

View Online at <https://aerobasegroup.com/nsn/5930-00-658-3867>

Thread Class:

2a single mounting facility

Thread Length:

0.245 inches single mounting facility and 0.255 inches single mounting facility

Overall Length:

Between 3.058 inches and 3.068 inches

Overall Height:

Between 2.307 inches and 2.317 inches

Overall Width:

Between 1.964 inches and 1.974 inches

First Flat Length:

0.245 inches 2nd actuator and 0.255 inches 2nd actuator

Flat Height:

0.214 inches 2nd actuator and 0.224 inches 2nd actuator

Shaft Diameter:

0.248 inches 1st actuator and 0.250 inches 1st actuator

Shaft Length:

0.870 inches 2nd actuator and 0.880 inches 2nd actuator

Individual Section Quantity:

4

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 4th section rear

Throw Quantity:

8 2nd section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

9 1st actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section front

Switch Actuator Positioning Increment:

15.0 degrees 2nd actuator

Detent Rotational Torque Range:

+20.000/+35.000 inch-ounces 1st actuator

Switch Actuator Stop Device Type:

Fixed stop 1st actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Precious Material And Location:

Contacts and rotors silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0