

View Online at <https://aerobasegroup.com/nsn/5930-00-658-3867>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.245 inches single mounting facility and 0.255 inches single mounting facility

**Overall Length:**

Between 3.058 inches and 3.068 inches

**Overall Height:**

Between 2.307 inches and 2.317 inches

**Overall Width:**

Between 1.964 inches and 1.974 inches

**First Flat Length:**

0.245 inches 2nd actuator and 0.255 inches 2nd actuator

**Flat Height:**

0.214 inches 2nd actuator and 0.224 inches 2nd actuator

**Shaft Diameter:**

0.248 inches 1st actuator and 0.250 inches 1st actuator

**Shaft Length:**

0.870 inches 2nd actuator and 0.880 inches 2nd actuator

**Individual Section Quantity:**

4

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 4th section rear

**Throw Quantity:**

8 2nd section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

9 1st actuator

**Shaft Type:**

Round, hollowed 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks each section front

**Switch Actuator Positioning Increment:**

15.0 degrees 2nd actuator

**Detent Rotational Torque Range:**

+20.000/+35.000 inch-ounces 1st actuator

**Switch Actuator Stop Device Type:**

Fixed stop 1st actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Contacts and rotors silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0