

View Online at <https://aerobasegroup.com/nsn/5930-00-658-7431>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.470 inches

Body Length:

0.984 inches

Body Width:

0.840 inches

Body Height:

Between 0.916 inches and 0.976 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.235 inches and 0.245 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Left position maintained and right position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

End Application:

2submarine interior communication system, iff aims mk xii, tarawa class lha, kilauea class t-ae 26, various shore atc, aircraft, c-18a, ec-18b, aircraft, sof (ac-130h, mc-130h, ec-130e, hc-130), aircraft, c-2a (reprocured), teletype, model 28

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 3.300 amperes motor ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0