

View Online at <https://aerobasegroup.com/nsn/5930-00-658-9611>

Body Style:

Bushing mounted

Overall Length:

0.906 inches

Overall Height:

1.540 inches

Overall Width:

0.781 inches

Bushing Length:

0.300 inches

Body Length:

0.906 inches

Body Width:

Between 0.771 inches and 0.791 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.318 inches and 0.328 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

Ticonderoga class c (47), virginia class cgn(41), tarawa class lha, spruance class dd(963) , gun 5-in/54 cal mk-42&45, wasp class lhd, kidd class ddg, arleigh burke class ddg

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0