

View Online at <https://aerobasegroup.com/nsn/5930-00-658-9611>

**Body Style:**

Bushing mounted

**Overall Length:**

0.906 inches

**Overall Height:**

1.540 inches

**Overall Width:**

0.781 inches

**Bushing Length:**

0.300 inches

**Body Length:**

0.906 inches

**Body Width:**

Between 0.771 inches and 0.791 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.318 inches and 0.328 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**End Application:**

Ticonderoga class c (47), virginia class cgn(41), tarawa class lha, spruance class dd(963) , gun 5-in/54 cal mk-42&45, wasp class lhd, kidd class ddg, arleigh burke class ddg

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

3 pole, double throw, both positions maintained single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0