

View Online at <https://aerobasegroup.com/nsn/5930-00-660-3945>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Weatherproof

**Overall Length:**

1.340 inches

**Overall Height:**

2.500 inches

**Overall Width:**

1.660 inches

**Bushing Length:**

Between 0.455 inches and 0.485 inches

**Body Length:**

1.340 inches

**Body Width:**

1.660 inches

**Body Height:**

Between 0.940 inches and 0.980 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.237 inches and 0.243 inches

**Actuator Height:**

Between 1.135 inches and 1.165 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 two circuit, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 15.000 amperes inductive dc and 4.000 amperes lamp dc and 20.000 amperes resistive ac and 12.000 amperes inductive ac and 5.000 amperes lamp ac

**Test Data Document:**

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0