

View Online at <https://aerobasegroup.com/nsn/5930-00-660-3949>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.470 inches

Body Length:

1.340 inches

Body Width:

0.890 inches

Body Height:

1.100 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Center position momentary and left position momentary and right position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

18.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 11.000 amperes resistive ac and 8.000 amperes inductive ac and 2.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0