

View Online at <https://aerobasegroup.com/nsn/5930-00-660-5421>

**Inside Diameter:**

0.250 inches single connection

**Overall Length:**

7.375 inches

**Overall Height:**

2.906 inches

**Overall Width:**

6.375 inches

**Body Length:**

5.500 inches

**Body Width:**

4.375 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

5.375 inches

**Longest Vertical Distance Between Mounting Centers:**

3.500 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

3000.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

10.0 amperes resistive load second voltage and 10.0 amperes inductive load second voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+90.00/+2500.00 actuation point pounds per square inch and +50.00/+2460.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point screw and internal deactuation point screw

**Contact Voltage Rating In Volts:**

460.0 ac at sea level third voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0