## NSN 5930-00-660-5421

Pressure Switch - Page 1 of 2

Inside Diameter:

0.250 inches single connection



View Online at https://aerobasegroup.com/nsn/5930-00-660-5421

Overall Length:
7.375 inches
Overall Height:
2.906 inches
Overall Width:
6.375 inches
Body Length:
5.500 inches
Body Width:
4.375 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
5.375 inches
Longest Vertical Distance Between Mounting Centers:
3.500 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Proof Pressure:
3000.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
10.0 amperes resistive load second voltage and 10.0 amperes inductive load second voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:
+90.00/+2500.00 actuation point pounds per square inch and +50.00/+2460.00 deactuation point pounds per square inch
Contact Adjustment Type:
Internal actuation point screw and internal deactuation point screw

## NSN 5930-00-660-5421

Pressure Switch - Page 2 of 2



## Contact Voltage Rating In Volts: 460.0 ac at sea level third voltage Pressure Connector Type: Plain, threaded internal single connection Media For Which Designed: Gas Style Designator: Rectangular w/bracket

Npt single pressure connection

**Thread Series Designator:** 

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A048b0