

View Online at <https://aerobasegroup.com/nsn/5930-00-661-0709>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Dustproof and watertight and vibration resistant

Overall Length:

5.188 inches

Overall Height:

5.687 inches

Overall Width:

2.812 inches

Body Height:

2.750 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

1.203 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

80.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

4.6 amperes resistive load fourth voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+1.00/+20.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Special Features:

0.250 in. Vent hole in box

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0