# NSN 5930-00-666-0153

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-666-0153

### **Thread Class:**

2a single mounting facility

### Thread Length:

0.375 inches single mounting facility

### **Overall Length:**

3.563 inches

#### **Overall Height:**

1.938 inches

#### **Overall Width:**

1.500 inches

#### Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

#### Shaft Length:

1.000 inches single actuator

#### **Nonturn Device Radius:**

0.531 inches at 10: 30 o'clock

## Individual Section Quantity:

3

#### Nonturn Device Type:

Tab at 10: 30 o'clock

### **Operating Tempurature Range:**

-25.0/+85.0 degrees celsius

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

3 each section rear

#### **Throw Quantity:**

3 each section rear

#### Mounting Method:

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

3 single actuator

#### Shaft Type:

Round single actuator

### **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Breaks before makes each section rear

# NSN 5930-00-666-0153

Rotary Switch - Page 2 of 2



**Switch Actuator Positioning Increment:** 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 500.0 milliamperes resistive load ac at sea level **Precious Material And Location:** Terminals and contact surfaces silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0