NSN 5930-00-666-0169

Rotary Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-00-666-0169 | | | |
|---|--|--|--|
| Thread Length: | | | |
| 1.156 inches single mounting facility | | | |
| Overall Length: | | | |
| 3.407 inches | | | |
| Overall Height: | | | |
| 1.875 inches | | | |
| Overall Width: | | | |
| 1.688 inches | | | |
| First Flat Length: | | | |
| 0.375 inches single actuator | | | |
| Flat Height: | | | |
| 0.344 inches single actuator | | | |
| Shaft Diameter: | | | |
| 0.250 inches single actuator | | | |
| Shaft Length: | | | |
| 1.719 inches single actuator | | | |
| Individual Section Quantity: | | | |
| 1 | | | |
| Switch Contact Basic Design: | | | |
| Nonpile-up symmetrical | | | |
| Pole Quantity: | | | |
| 4 single section front | | | |
| Throw Quantity: | | | |
| 2 single section front | | | |
| Mounting Method: | | | |
| Threaded bushing single mounting facility | | | |
| Thread Size: | | | |
| 0.375 inches single mounting facility | | | |
| Contact Voltage Rating In Volts: | | | |
| 300.0 highest ac voltage rating at sea level | | | |
| Switch Actuator Indexing Position Quantity: | | | |
| 2 single actuator | | | |
| Shaft Type: | | | |
| Round, flatted single actuator | | | |
| Terminal Type: | | | |
| Tab, solder lug | | | |
| Contact Switching Action: | | | |
| Makes before breaks single section front | | | |
| Switch Actuator Positioning Increment: | | | |
| 30.0 degrees single actuator | | | |
| Contact Load Current Rating: | | | |

600.0 milliamperes resistive load highest ac voltage rating at sea level

NSN 5930-00-666-0169

Rotary Switch - Page 2 of 2



| Thread | Series | Design | ator |
|--------|---------------|--------|------|
| | | | |

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0