

View Online at <https://aerobasegroup.com/nsn/5930-00-666-1927>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Watertight

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.875 inches

Body Width:

0.688 inches

Body Height:

0.875 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.138 inches

Actuator Style:

Round

Actuator Diameter:

0.328 inches

Actuator Height:

1.250 inches

Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing and unthreaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 9.0 ounces and 24.0 ounces

Actuator Movement:

Between 0.094 pretravel inches and 0.218 overtravel inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Special Features:

Rubber cap

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0