

View Online at <https://aerobasegroup.com/nsn/5930-00-669-7344>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

3.187 inches

**Actuator Style:**

Roller arm

**Housing Height:**

Between 1.235 inches and 1.265 inches

**Housing Length:**

Between 2.485 inches and 2.515 inches

**Housing Width:**

Between 1.204 inches and 1.234 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

Between 1.548 inches and 1.578 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

Between 1.860 inches and 1.890 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 two circuit, double make, two positions momentary single switch unit

**Switch Actuating Force:**

Between 64.0 ounces and 66.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 6.000 amperes lamp ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0