NSN 5930-00-669-7420

Hazardous Locations/environmental Protection:

Longest Horizontal Distance Between Mounting Centers:

Rotary Switch - Page 1 of 2

Thread Class:

Dustproof

20

Overall Length: 10.781 inches Overall Height: 2.812 inches Overall Width: 2.812 inches Shaft Length:

2b single mounting facility

1.156 inches single actuator Individual Section Quantity:



View Online at https://aerobasegroup.com/nsn/5930-00-669-7420

2.297 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.297 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section periphery **Throw Quantity:** 7 each section periphery **Mounting Method:** Threaded hole single mounting facility Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 8 single actuator **Shaft Type:** Rectangular/square, threaded hole single actuator **Square Shaft Size:** 0.250 inches single actuator **Terminal Type:** Tab w/screw

NSN 5930-00-669-7420

Rotary Switch - Page 2 of 2



Contact	Switching	Action:
Joniaci	Switching	ACLION.

Makes before breaks, breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0