

View Online at <https://aerobasegroup.com/nsn/5930-00-669-7448>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

3.187 inches

Actuator Length:

Between 1.828 inches and 1.858 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

2.969 inches

Actuator Roller Diameter:

Between 0.485 inches and 0.515 inches

Housing Height:

Between 1.235 inches and 1.265 inches

Housing Length:

Between 2.485 inches and 2.515 inches

Housing Width:

Between 1.204 inches and 1.234 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

Between 1.548 inches and 1.578 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

Between 1.860 inches and 1.890 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Switch Actuating Force:

Between 64.0 ounces and 66.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 6.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0