

View Online at <https://aerobasegroup.com/nsn/5930-00-669-7467>

Body Style:

Hole mounted

Unthreaded Mounting Hole Diameter:

1.040 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.906 inches

Actuator Free Position Height:

2.484 inches

Housing Height:

1.531 inches

Housing Length:

2.090 inches

Housing Width:

1.031 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.687 inches

Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

End Application:

C130/f15/t37/t38/sof aircraft

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

80.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.250 overtravel inches and 0.031 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 3.000 amperes resistive ac

Special Features:

Actuator sealed w/boot dust and moisture seal

Precious Material And Location:

Gold plating gold

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0