

View Online at <https://aerobasegroup.com/nsn/5930-00-669-7467>

**Body Style:**

Hole mounted

**Unthreaded Mounting Hole Diameter:**

1.040 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.906 inches

**Actuator Free Position Height:**

2.484 inches

**Housing Height:**

1.531 inches

**Housing Length:**

2.090 inches

**Housing Width:**

1.031 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

1.687 inches

**Maximum Voltage Rating In Volts:**

460.0 ac and 250.0 dc

**End Application:**

C130/f15/t37/t38/sof aircraft

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

8.0 ounces

**Switch Actuating Force:**

80.0 ounces

**Actuator Movement:**

Between 0.078 pretravel inches and 0.250 overtravel inches and 0.031 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

400.000 milliamperes resistive dc and 3.000 amperes resistive ac

**Special Features:**

Actuator sealed w/boot dust and moisture seal

**Precious Material And Location:**

Gold plating gold

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A053a0