## NSN 5930-00-669-7479

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-669-7479

View Online at https://aerobasegroup.com/nsn/5930-00-669-7479
Overall Length:
0.687 inches
Overall Height:
0.694 inches
Body Diameter:
0.640 inches
Body Height:
0.422 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
0.444 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -10.0 degrees fahrenheit and 250.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action
1 pole, single throw, normally closed, momentary action
1 pole, single throw, normally closed, momentary action Terminal Type:
1 pole, single throw, normally closed, momentary action <b>Terminal Type:</b> Tab, solder lug
1 pole, single throw, normally closed, momentary action <b>Terminal Type:</b> Tab, solder lug <b>Contact Load Current Rating:</b>
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability:
<ul> <li>1 pole, single throw, normally closed, momentary action</li> <li>Terminal Type:</li> <li>Tab, solder lug</li> <li>Contact Load Current Rating:</li> <li>5.0 amperes resistive load third voltage</li> <li>Contact Adjustability:</li> <li>Deactuation point not adjustable and actuation point not adjustable</li> </ul>
<ol> <li>pole, single throw, normally closed, momentary action</li> <li>Terminal Type:</li> <li>Tab, solder lug</li> <li>Contact Load Current Rating:</li> <li>5.0 amperes resistive load third voltage</li> <li>Contact Adjustability:</li> <li>Deactuation point not adjustable and actuation point not adjustable</li> <li>Contact Stimulus Rating:</li> </ol>
<ol> <li>pole, single throw, normally closed, momentary action</li> <li>Terminal Type:         <ul> <li>Tab, solder lug</li> <li>Contact Load Current Rating:</li> <li>5.0 amperes resistive load third voltage</li> <li>Contact Adjustability:</li> <li>Deactuation point not adjustable and actuation point not adjustable</li> <li>Contact Stimulus Rating:</li> <li>70.00 actuation point degrees fahrenheit and 50.00 deactuation point degrees fahrenheit</li> </ul> </li> </ol>
<ul> <li>1 pole, single throw, normally closed, momentary action</li> <li>Terminal Type:</li> <li>Tab, solder lug</li> <li>Contact Load Current Rating:</li> <li>5.0 amperes resistive load third voltage</li> <li>Contact Adjustability:</li> <li>Deactuation point not adjustable and actuation point not adjustable</li> <li>Contact Stimulus Rating:</li> <li>70.00 actuation point degrees fahrenheit and 50.00 deactuation point degrees fahrenheit</li> <li>Contact Voltage Rating In Volts:</li> </ul>
<ul> <li>1 pole, single throw, normally closed, momentary action</li> <li>Terminal Type:</li> <li>Tab, solder lug</li> <li>Contact Load Current Rating:</li> <li>5.0 amperes resistive load third voltage</li> <li>Contact Adjustability:</li> <li>Deactuation point not adjustable and actuation point not adjustable</li> <li>Contact Stimulus Rating:</li> <li>70.00 actuation point degrees fahrenheit and 50.00 deactuation point degrees fahrenheit</li> <li>Contact Voltage Rating In Volts:</li> <li>30.0 dc at sea level third voltage</li> </ul>
<ul> <li>1 pole, single throw, normally closed, momentary action</li> <li>Terminal Type: <ul> <li>Tab, solder lug</li> </ul> </li> <li>Contact Load Current Rating:</li> <li>5.0 amperes resistive load third voltage</li> <li>Contact Adjustability:</li> <li>Deactuation point not adjustable and actuation point not adjustable</li> <li>Contact Stimulus Rating:</li> <li>70.00 actuation point degrees fahrenheit and 50.00 deactuation point degrees fahrenheit</li> <li>Contact Voltage Rating In Volts:</li> <li>30.0 dc at sea level third voltage</li> <li>Media For Which Designed:</li> </ul>
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 70.00 actuation point degrees fahrenheit and 50.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Media For Which Designed: Gas or liquid
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 70.00 actuation point degrees fahrenheit and 50.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Media For Which Designed: Gas or liquid Style Designator:
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 70.00 actuation point degrees fahrenheit and 50.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Media For Which Designed: Gas or liquid Style Designator: Disc w/flange

---

## NSN 5930-00-669-7479

Thermostatic Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A048b0

