

View Online at <https://aerobasegroup.com/nsn/5930-00-669-7498>

Overall Length:

8.687 inches

First Flat Length:

0.531 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.062 inches single actuator

Overall Diameter:

4.188 inches

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

2.375 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.687 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.062 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

4 each section rear

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

300.0 ac at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

50.0 amperes resistive load ac at sea level

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0