## NSN 5930-00-669-7725

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-669-7725

Maximum Voltage Rating In Volts:  125.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement:  1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.529 inch-ounces Switch Actuating Force: 1.551 inch-ounces Actuator Movement: Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Actuator Free Position Height:
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.529 inch-ounces Switch Actuating Force: 1.551 inch-ounces Actuator Movement: Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.219 inches
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 0.529 inch-ounces Switch Actuating Force: 1.551 inch-ounces Actuator Movement: Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	Maximum Voltage Rating In Volts:
Fully enclosed  Nonpile-up Contact Arrangement:  1 pole, double throw, one position momentary single switch unit  Switch Release Force:  0.529 inch-ounces  Switch Actuating Force:  1.551 inch-ounces  Actuator Movement:  Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  3.000 amperes resistive ac  Terminal Type And Quantity:  3 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	125.0 ac
Nonpile-up Contact Arrangement:  1 pole, double throw, one position momentary single switch unit  Switch Release Force:  0.529 inch-ounces  Switch Actuating Force:  1.551 inch-ounces  Actuator Movement:  Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  3.000 amperes resistive ac  Terminal Type And Quantity:  3 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Inclosure Type:
1 pole, double throw, one position momentary single switch unit  Switch Release Force: 0.529 inch-ounces  Switch Actuating Force: 1.551 inch-ounces  Actuator Movement: Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	Fully enclosed
Switch Release Force:  0.529 inch-ounces  Switch Actuating Force:  1.551 inch-ounces  Actuator Movement:  Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  3.000 amperes resistive ac  Terminal Type And Quantity:  3 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Nonpile-up Contact Arrangement:
O.529 inch-ounces  Switch Actuating Force:  1.551 inch-ounces  Actuator Movement:  Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  3.000 amperes resistive ac  Terminal Type And Quantity:  3 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	1 pole, double throw, one position momentary single switch unit
Switch Actuating Force:  1.551 inch-ounces  Actuator Movement:  Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  3.000 amperes resistive ac  Terminal Type And Quantity:  3 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Switch Release Force:
1.551 inch-ounces  Actuator Movement:  Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	0.529 inch-ounces
Actuator Movement:  Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  3.000 amperes resistive ac  Terminal Type And Quantity:  3 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Switch Actuating Force:
Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	1.551 inch-ounces
Contact Load Current Rating At Maximum Rated Voltage:  3.000 amperes resistive ac  Terminal Type And Quantity:  3 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Actuator Movement:
3.000 amperes resistive ac  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches
Terminal Type And Quantity:  3 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Contact Load Current Rating At Maximum Rated Voltage:
3 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	3.000 amperes resistive ac
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No	3 tab, solder lug
Unit Of Measure: Demilitarization: No	Shelf Life:
Demilitarization: No	N/a
No	Unit Of Measure:
No	-
	Demilitarization:
Fiig:	No
	Fiig:
A053a0	A053a0