

View Online at <https://aerobasegroup.com/nsn/5930-00-669-7961>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.594 inches

**First Flat Length:**

0.500 inches single actuator

**Flat Height:**

0.188 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.750 inches single actuator

**Individual Section Quantity:**

2

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

3 each section rear

**Mounting Facility Circle Radius:**

1.151 inches single mounting facility

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 highest dc voltage rating at sea level

**Mounting Facility Pattern:**

Four position circular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load lowest ac voltage rating at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0