

View Online at <https://aerobasegroup.com/nsn/5930-00-669-8129>

Body Style:

Hole mounted

Overall Length:

1.688 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.520 inches

Overall Height:

0.500 inches

Overall Width:

0.594 inches

Body Length:

1.250 inches

Body Width:

0.500 inches

Body Height:

0.500 inches

Unthreaded Mounting Hole Diameter:

Between 0.101 inches and 0.104 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.312 inches

Actuator Length:

0.250 inches

Actuator Style:

Rectangular

Actuator Height:

0.094 inches

Actuator Width:

0.297 inches

Actuator Free Position Height:

0.146 inches

Maximum Voltage Rating In Volts:

250.0 ac and 125.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 9.0 ounces and 15.0 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.015 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 10.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0