

View Online at <https://aerobasegroup.com/nsn/5930-00-669-8226>

Overall Length:

1.870 inches

Overall Height:

2.250 inches

Overall Width:

1.750 inches

Shaft Length:

0.420 inches single actuator

Unthreaded Mounting Hole Diameter:

0.193 inches single mounting facility and 0.195 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.380 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Base single mounting facility and unthreaded hole single mounting facility

Features Provided:

Cam actuated

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position diagonal single mounting facility

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, both positions maintained single switch single section rear

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, fluted, threaded hole single actuator

Terminal Type:

Wire lead

Contact Switching Action:

Makes before breaks, breaks before makes single section rear

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level and 5.0 amperes inductive load dc at sea level

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A052b0