NSN 5930-00-669-8283

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-669-8283	
Body Style:	
Hole mounted	
Overall Length:	
1.094 inches	
Center To Center Distance Between Mounting Facilities Parallel To Length:	
Between 0.872 inches and 0.878 inches	
Overall Height:	
0.780 inches	
Overall Width:	
0.406 inches	
Body Length:	
Between 1.084 inches and 1.104 inches	
Body Width:	
Between 0.396 inches and 0.416 inches	
Body Height:	
Between 0.615 inches and 0.635 inches	
Case Material:	
Plastic	
Unthreaded Mounting Hole Diameter:	
Between 0.113 inches and 0.116 inches	
Actuator Length:	
0.110 inches	
Actuator Style:	
Rectangular	
Actuator Height:	
0.047 inches	
Actuator Width:	
0.165 inches	
Maximum Voltage Rating In Volts:	
250.0 ac and 250.0 dc	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Unthreaded hole	
Nonpile-up Contact Arrangement:	
1 pole, single throw, normally open, momentary action single switch unit	
Switch Release Force:	

4.0 ounces

Switch Actuating Force:

14.0 ounces

Actuator Movement:

Between 0.046 pretravel inches and 0.031 overtravel inches and 0.016 differential inches

NSN 5930-00-669-8283

Sensitive Switch - Page 2 of 2



	Contact Load	Current Ra	ating At	Maximum	Rated V	oltage:
--	--------------	-------------------	----------	---------	---------	---------

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

1 screw and 2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0