NSN 5930-00-669-9989

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-669-9989

Т	hr	ea	d	CI	as	S	•

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

11.395 inches

Overall Height:

2.812 inches

Overall Width:

2.812 inches

Shaft Length:

2.275 inches single actuator

Individual Section Quantity:

21

Longest Horizontal Distance Between Mounting Centers:

2.297 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.297 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

8 each section periphery

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.247 inches single actuator

Terminal Type:

Tab w/screw

NSN 5930-00-669-9989 Rotary Switch - Page 2 of 2



Contact Switching Action:					
Breaks before makes each section periphery					
Switch Actuator Positioning Increment:					
45.0 degrees single actuator					
Switch Actuator Stop Device Type:					
Adjustable stop single actuator					
Contact Load Current Rating:					
5.0 amperes resistive load dc at sea level					
Special Features:					
Shaft undercut 0.125 in.					
Style Designator:					
Tap, circuit selector					
Thread Series Designator:					
Unc single mounting facility					
Shelf Life:					
N/a					
Unit Of Measure:					
Demilitarization:					

No Fiig: A052b0