

View Online at <https://aerobasegroup.com/nsn/5930-00-670-3804>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.469 inches

Body Length:

1.438 inches

Body Width:

1.328 inches

Body Height:

1.219 inches

Actuator Style:

Round

Actuator Height:

0.688 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

440.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.468 inches

Nonpile-up Contact Arrangement:

4 pole, single throw, normally open, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes motor dc and 3.000 amperes resistive ac and 2.200 amperes inductive ac and 2.000 amperes motor ac

Special Features:

Modified with internal circuit and jumpers

Test Data Document:

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0