NSN 5930-00-670-9701

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-670-9701

Thread Length:	Th	read	Leng	įth:
----------------	----	------	------	------

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof and explosion proof

First Flat Length:

0.250 inches single actuator

Flat Height:

0.220 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.560 inches single actuator

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

2 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5930-00-670-9701

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0