

View Online at <https://aerobasegroup.com/nsn/5930-00-674-9681>

Thread Class:

2b single mounting facility

Overall Length:

4.625 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

Shaft Diameter:

0.249 inches single actuator and 0.250 inches single actuator

Shaft Length:

1.125 inches single actuator

Unthreaded Mounting Hole Diameter:

0.168 inches single mounting facility and 0.174 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.500 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

0.750 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.500 inches single mounting facility

Shortest Vertical Distance Between Mounting Centers:

0.750 inches single mounting facility

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

24 each section rear

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility and unthreaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Rotor Through Connection Quantity:

1 each section

Mounting Facility Pattern:

Four position diamond single mounting facility

Switch Actuator Indexing Position Quantity:

24 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts and terminals silver

Precious Material:

Silver

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0