

View Online at <https://aerobasegroup.com/nsn/5930-00-675-7466>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.312 inches single mounting facility

**Overall Length:**

4.260 inches

**Overall Height:**

1.880 inches

**Overall Width:**

1.620 inches

**First Flat Length:**

0.340 inches 2nd actuator

**Flat Height:**

0.218 inches 1st actuator

**Shaft Diameter:**

0.265 inches 1st actuator

**Shaft Length:**

1.200 inches 2nd actuator

**Nonturn Device Radius:**

0.781 inches at 12: 00 o'clock

**Individual Section Quantity:**

6

**Nonturn Device Type:**

Tab at 12: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

20 all actuators

**Shaft Type:**

Round, hollowed, flatted 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks each section rear

**Switch Actuator Positioning Increment:**

18.0 degrees all actuators

**Switch Actuator Stop Device Type:**

Fixed stop all actuators

**Contact Load Current Rating:**

75.0 milliamperes resistive load ac at sea level

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0