

View Online at <https://aerobasegroup.com/nsn/5930-00-675-7466>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

4.260 inches

Overall Height:

1.880 inches

Overall Width:

1.620 inches

First Flat Length:

0.340 inches 2nd actuator

Flat Height:

0.218 inches 1st actuator

Shaft Diameter:

0.265 inches 1st actuator

Shaft Length:

1.200 inches 2nd actuator

Nonturn Device Radius:

0.781 inches at 12: 00 o'clock

Individual Section Quantity:

6

Nonturn Device Type:

Tab at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

20 all actuators

Shaft Type:

Round, hollowed, flatted 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

18.0 degrees all actuators

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

75.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0