NSN 5930-00-676-0064

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-676-0064

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

1.917 inches

Shaft Diameter:

0.243 inches 1st actuator and 0.251 inches 1st actuator

Shaft Length:

1.197 inches 2nd actuator

Overall Diameter:

1.010 inches

Individual Section Quantity:

.

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

2 1st actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

72.0 degrees 1st actuator

Switch Actuator Stop Device Type:

Fixed stop 1st actuator

NSN 5930-00-676-0064

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

1.0 amperes resistive load dc at sea level and 100.0 milliamperes inductive load dc at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0