# NSN 5930-00-676-5690

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-676-5690

# Thread Length:

0.250 inches single mounting facility

# **Hazardous Locations/environmental Protection:**

Dustproof

# First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.220 inches single actuator

#### **Shaft Diameter:**

0.250 inches single actuator

#### **Shaft Length:**

0.560 inches single actuator

#### **Individual Section Quantity:**

6

#### **Switch Contact Basic Design:**

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section front

# **Throw Quantity:**

8 each section rear

# **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

# **Contact Voltage Rating In Volts:**

115.0 ac at sea level

# **Rotor Through Connection Quantity:**

1 each section

# **Switch Actuator Indexing Position Quantity:**

8 single actuator

# Shaft Type:

Round, flatted single actuator

# **Terminal Type:**

Tab, solder lug

# **Contact Switching Action:**

Breaks before makes each section front

# **Switch Actuator Positioning Increment:**

36.0 degrees single actuator

# **Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

# **Thread Series Designator:**

Unef single mounting facility

# NSN 5930-00-676-5690

Rotary Switch - Page 2 of 2



		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0