

View Online at <https://aerobasegroup.com/nsn/5930-00-677-0902>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.365 inches single mounting facility and 0.385 inches single mounting facility

**Overall Length:**

Between 1.866 inches and 1.886 inches

**Overall Height:**

Between 1.552 inches and 1.572 inches

**Overall Width:**

Between 1.302 inches and 1.322 inches

**First Flat Length:**

0.428 inches single actuator and 0.448 inches single actuator

**Flat Height:**

0.216 inches single actuator and 0.220 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.928 inches single actuator and 0.948 inches single actuator

**Nonturn Device Radius:**

0.521 inches at 2: 00 o'clock and 0.541 inches at 2: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 2: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 single section front

**Throw Quantity:**

9 single section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

15.0 dc at sea level

**Shaft Flat/slot Angular Location:**

95.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0