

View Online at <https://aerobasegroup.com/nsn/5930-00-677-3938>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.625 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.707 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.937 inches single actuator

**Overall Diameter:**

1.125 inches

**Individual Section Quantity:**

3

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

4 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 lowest dc voltage rating at sea level

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load lowest dc voltage rating at sea level and 500.0 milliamperes inductive load lowest dc voltage rating at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0