

View Online at <https://aerobasegroup.com/nsn/5930-00-678-0096>

Thread Length:

0.359 inches single mounting facility and 0.391 inches single mounting facility

Overall Length:

Between 1.703 inches and 1.735 inches

First Flat Length:

0.296 inches single actuator and 0.328 inches single actuator

Flat Height:

0.088 inches single actuator and 0.098 inches single actuator

Shaft Diameter:

0.123 inches single actuator and 0.125 inches single actuator

Shaft Length:

0.734 inches single actuator and 0.766 inches single actuator

Overall Diameter:

1.125 inches

Nonturn Device Radius:

0.359 inches at 11: 00 o'clock and 0.391 inches at 11: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 11: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

6 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Shaft Flat/slot Angular Location:

90.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0