NSN 5930-00-678-0438

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-678-0438

| Thread Length: |
|---|
| 0.375 inches single mounting facility |
| Overall Length: |
| 2.062 inches |
| Overall Height: |
| 1.625 inches |
| Overall Width: |
| 1.250 inches |
| First Flat Length: |
| 0.312 inches single actuator |
| Flat Height: |
| 0.093 inches single actuator |
| Shaft Diameter: |
| 0.125 inches single actuator |
| Shaft Length: |
| 0.750 inches single actuator |
| Nonturn Device Radius: |
| 0.375 inches at 10: 30 o'clock |
| Individual Section Quantity: |
| 2 |
| Nonturn Device Type: |
| Tab at 10: 30 o'clock |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section rear |
| Throw Quantity: |
| 8 each section rear |
| Mounting Method: |
| Threaded bushing single mounting facility |
| Thread Size: |
| 0.250 inches single mounting facility |
| Shaft Flat/slot Angular Location: |
| 105.0 degrees from nonturn device single actuator |
| Switch Actuator Indexing Position Quantity: |
| 8 single actuator |
| Shaft Type: |
| Round, flatted single actuator |
| Terminal Type: |

Contact Switching Action:

Tab, solder lug

Breaks before makes each section rear

NSN 5930-00-678-0438

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0