

View Online at <https://aerobasegroup.com/nsn/5930-00-678-1112>

Overall Length:

2.250 inches

Overall Diameter:

1.680 inches

Pressure Switch Type:

Gage

Mounting Method:

Inlet connection

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

225.00 pounds per square inch

Terminal Type:

Tab w/screw

Contact Load Current Rating:

4.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+15.00/+60.00 actuation point pounds per square inch and +15.00/+60.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

35.00 actuation point pounds per square inch and 37.00 deactuation point pounds per square inch and 2.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

6.0 dc at sea level second voltage

Pressure Connector Type:

Flareless, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0