

View Online at <https://aerobasegroup.com/nsn/5930-00-678-1630>

**Body Style:**

Hole mounted

**Overall Length:**

1.060 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.750 inches

**Overall Height:**

1.050 inches

**Overall Width:**

0.750 inches

**Body Length:**

1.060 inches

**Body Width:**

0.560 inches

**Body Height:**

0.810 inches

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.500 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.115 inches and 0.125 inches

**Actuator Height:**

0.190 inches

**Actuator Free Position Height:**

0.160 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 inch-ounces

**Switch Actuating Force:**

4.0 inch-ounces

**Actuator Movement:**

20.0 pretravel degrees and 20.0 overtravel degrees and 30.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac

**Special Features:**

Screw driver slotted actuator, 0.125 in. Dia, 0.049 in. H, 0.062 in. W

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0