

View Online at <https://aerobasegroup.com/nsn/5930-00-678-1630>

Body Style:

Hole mounted

Overall Length:

1.060 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.750 inches

Overall Height:

1.050 inches

Overall Width:

0.750 inches

Body Length:

1.060 inches

Body Width:

0.560 inches

Body Height:

0.810 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.115 inches and 0.125 inches

Actuator Height:

0.190 inches

Actuator Free Position Height:

0.160 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 inch-ounces

Switch Actuating Force:

4.0 inch-ounces

Actuator Movement:

20.0 pretravel degrees and 20.0 overtravel degrees and 30.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac

Special Features:

Screw driver slotted actuator, 0.125 in. Dia, 0.049 in. H, 0.062 in. W

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0