NSN 5930-00-678-2946

Sensitive Switch - Page 1 of 2

170.0 ounces



View Online at https://aerobasegroup.com/nsn/5930-00-678-2946

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
0.876 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.357 inches
Overall Width:
0.346 inches
Body Length:
0.876 inches
Body Width:
0.346 inches
Body Height:
0.600 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Height:
0.050 inches
Actuator Free Position Height:
0.425 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:

NSN 5930-00-678-2946

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0