NSN 5930-00-678-9910

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-678-9910

Thread Class: 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 1.682 inches **Overall Height:** 1.046 inches **Overall Width:** 1.000 inches First Flat Length: 0.250 inches single actuator Flat Height: 0.216 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.875 inches single actuator **Overall Diameter:** 1.046 inches **Individual Section Quantity:** 1 **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 5 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 5 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug

Contact Switching Action:Breaks before makes single section rear

NSN 5930-00-678-9910

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

2.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0