NSN 5930-00-679-4830

Liquid Level Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-679-4830

Overall Length:
10.280 inches
Dc Voltage Rating:
28.0 volts
Overall Diameter:
4.610 inches
Connector Manufacturer Code:
71648
Actuation Method:
Buoyancy
Electrical Connection Type:
Connector receptacle
Connector Identification:
Gs02-14s-7p-001
Current Rating At Maximum Rated Voltage:
3.0 amperes load
Float Quantity:
1
Operating Tempurature Rating:
Between -85.0 degrees fahrenheit and 160.0 degrees fahrenheit
Mounting Method:
Flange
Mounting Position:
Vertical
Contact Arrangement:
Spdt, normally closed
Relay:
Not included
Liquid Type For Which Designed:
Aircraft fuel
Aircraft Fuel For Which Designed:
Specific
Aircraft Fuel Grade Specificationification:
Mil-g-5572c and mil-j-5624f
Aircraft Fuel Grade:
80/87, 91/96, 100/130, 115/145 and jp-4, jp-5
Aircraft Fuel Grade Specificationific Gravity Rating:
0.845 at 15.6 degrees c, max sp gr

Float Effective Travel:

Between 0.750 inches and 1.250 inches

Mounting Dimensions:

Mtd by six 0.320 in. Diameter holes equally spaced on a 2 in. Radius

NSN 5930-00-679-4830

Liquid Level Switch - Page 2 of 2



8.530 inches
Float And Contact Positions:
Float down, contacts closed
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Tank Insertion Length:

Mil-std (military Standard): Mil-g-5572 spec.

T109-d