NSN 5930-00-679-9498

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-679-9498

Thread Class: 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 2.625 inches **Overall Height:** 1.312 inches **Overall Width:** 1.297 inches **Shaft Diameter:** 0.248 inches single actuator and 0.250 inches single actuator **Shaft Length:** 1.500 inches single actuator **Nonturn Device Radius:** 0.531 inches at 3: 00 o'clock **Individual Section Quantity:** 2 **Nonturn Device Type:** Tab at 3: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical and nonpile-up nonsymmetrical **Pole Quantity:** 4 1st section rear **Throw Quantity:** 2 1st section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:**

60.0 degrees single actuator

NSN 5930-00-679-9498

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0