

View Online at <https://aerobasegroup.com/nsn/5930-00-681-0594>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.624 inches

Overall Height:

2.125 inches

Overall Width:

1.812 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.156 inches single actuator

Unthreaded Mounting Hole Diameter:

0.188 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.437 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.750 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks, breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0