Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-681-0594

Hazardous Locations/environmental Protection:

Dustproof

**Overall Length:** 

2.624 inches

# **Overall Height:**

2.125 inches

# Overall Width:

1.812 inches

# First Flat Length:

0.500 inches single actuator

Flat Height:

0.219 inches single actuator

### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

1.156 inches single actuator

### Unthreaded Mounting Hole Diameter:

0.188 inches single mounting facility

### Individual Section Quantity:

2

# Longest Horizontal Distance Between Mounting Centers:

1.437 inches single mounting facility

# Longest Vertical Distance Between Mounting Centers:

1.750 inches single mounting facility

# Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

# Contact Voltage Rating In Volts:

30.0 dc at sea level

# Mounting Facility Pattern:

Four position rectangular single mounting facility

# Switch Actuator Indexing Position Quantity:

2 single actuator

#### Shaft Type:

Round, flatted single actuator

# Terminal Type:

Tab w/screw

#### **Contact Switching Action:**

Makes before breaks, breaks before makes each section periphery

#### Switch Actuator Positioning Increment:

45.0 degrees single actuator

# NSN 5930-00-681-0594

Rotary Switch - Page 2 of 2



## **Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level

## Style Designator:

Tap, circuit selector

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A052b0