## NSN 5930-00-681-0595

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-681-0595

view Offiline at https://defobasegroup.com/histi/0550-00-001-0555
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
3.374 inches
Overall Height:
2.125 inches
Overall Width:
1.812 inches
First Flat Length:
0.500 inches single actuator
Flat Height:
0.219 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.156 inches single actuator
Unthreaded Mounting Hole Diameter:
0.188 inches single mounting facility
Individual Section Quantity:
4
Longest Horizontal Distance Between Mounting Centers:
1.437 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.750 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Contact Voltage Rating In Volts:
30.0 dc at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Makes before breaks, breaks before makes each section periphery

45.0 degrees single actuator

**Switch Actuator Positioning Increment:** 

## NSN 5930-00-681-0595

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level

**Style Designator:** 

Tap, circuit selector

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A052b0