

View Online at <https://aerobasegroup.com/nsn/5930-00-681-0619>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.999 inches

**Overall Height:**

2.125 inches

**Overall Width:**

1.812 inches

**First Flat Length:**

0.500 inches single actuator

**Flat Height:**

0.218 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.156 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.188 inches single mounting facility

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

1.437 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.750 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

4 each section rear

**Mounting Method:**

Unthreaded hole single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0