Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-681-0622

Hazardous Locations/environmental Protection:

Dustproof

**Overall Length:** 

3.905 inches

# **Overall Height:**

2.125 inches

# Overall Width:

2.000 inches

## First Flat Length:

0.500 inches single actuator

Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

0.562 inches single actuator

# Unthreaded Mounting Hole Diameter:

# 0.188 inches single mounting facility

# Individual Section Quantity:

```
7
```

## Longest Horizontal Distance Between Mounting Centers:

1.437 inches single mounting facility

# Longest Vertical Distance Between Mounting Centers:

1.750 inches single mounting facility

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

2 each section rear

#### **Throw Quantity:**

4 each section rear

## **Mounting Method:**

Unthreaded hole single mounting facility

## Contact Voltage Rating In Volts:

30.0 dc at sea level

## Mounting Facility Pattern:

Four position rectangular single mounting facility

## Switch Actuator Indexing Position Quantity:

4 single actuator

## Shaft Type:

Round, v flatted single actuator

## **Terminal Type:**

Tab w/screw

## **Contact Switching Action:**

Breaks before makes each section rear

# NSN 5930-00-681-0622

Rotary Switch - Page 2 of 2



#### Switch Actuator Positioning Increment:

45.0 degrees single actuator

#### **Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level

#### Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0