NSN 5930-00-681-3081

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-681-3081

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
3.187 inches
Overall Height:
2.125 inches
Overall Width:
1.812 inches
First Flat Length:
0.500 inches single actuator
Flat Height:
0.218 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.156 inches single actuator
Unthreaded Mounting Hole Diameter:
0.188 inches single mounting facility
Individual Section Quantity:
3
Longest Horizontal Distance Between Mounting Centers:
1.438 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.750 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section rear
Throw Quantity:
3 each section rear
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Contact Voltage Rating In Volts:
125.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Round, flatted single actuator
Terminal Type:

Tab w/screw

NSN 5930-00-681-3081

Rotary Switch - Page 2 of 2



Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0